2016 SEVENTY-TWO®

XL 1200V

Truly Accessible, Chopper-Inspired Authentic Custom

Model shown in HDI configuration.

The vehicle models, configurations, options, and accessories pictured or otherwise described in this reference guide may not be available in all countries.



Markets: APC, AUS, MEX, ENG, HDI, JPN

2016 SEVENTY-TWO®
XL 1200V
MODEL OVERVIEW

MODEL OVERVIEW

Authentic '70s chopper attitude meets modern power in the Seventy-Two® motorcycle, a bare-bones, lowrider-inspired radical custom. With its Hard Candy Custom™ paint options, peanut tank, round retro-style air-cleaner cover, ape-hanger handlebars, and whitewall tires, the bike screams high-end custom.

NEW IN 2016

- Emulsion technology rear shocks with 50 mm range of pre-load adjustability and an under-seat, rear shock suspension adjustment wrench
- Front forks with cartridge dampening technology
- Optimised seat design for all-day comfort, minimalist style
- Paint color options including Hard Candy Custom™ colors

MODEL UNIQUE FEATURES

Style

- Chrome, staggered, shorty exhaust with dual slash-cut mufflers
- Chrome Steel Laced wheels with custom whitewall tires, 21-inch front, 16-inch rear
- Stainless steel, mini ape-hanger handlebar
- 7.9L Peanut Tank with lightening-hole mounting bracket
- Minimalistic solo seat
- Chopped rear fender

MODEL UNIQUE FEATURES *(continued)*

Style *(continued)*

- Chrome, 203.2 mm round air cleaner
- Chrome engine covers
- Chrome primary cover
- Chrome rear shocks
- Chrome fender strut covers
- Chrome speedo
- Chrome headlight
- Chrome bullet combined stop/turn/tail lights
- Engine turn graphic on timer cover
- Fork brace with lightening holes
- Side-mounted license plate (except HDI)

Fit

- Forward-mounted controls
- 730 mm seat height
- Stainless steel, mini-ape handlebar

Function

- Integrated electrical system with trip switch, start switch
- 101.6 mm speedometer mounted on handlebar
  - Electronic speedometer with odometer, time-of-day clock on odometer, dual tripmeter, LED indicator lights, gear indicator (1-5), and RPMs
- Hazard warning integrated into self-canceling turn signal controls
- Blade key ignition; fork lock common with ignition key
- Dunlop® Harley-Davidson® Series narrow whitewall tires
- Closed loop exhaust system meets worldwide emission standards

MODEL UNIQUE FEATURES *(continued)*

Performance

- Rubber-mounted, Air-cooled 1202 cc Evolution® engine
- Electronic Sequential Port Fuel Injection (ESPFI) with O2 sensors
- 5-speed transmission
- Confidence-inspiring braking performance
- Anti-lock Braking System (ABS)[1], standard

AVAILABLE OPTIONS

- Smart Security System[2] with hands-free, proximity based security fob and keyless ignition (factory installed option)

[1] Harley-Davidson's independent Anti-lock Braking System is designed to help you maintain control during braking events, especially those that happen in less than optimum conditions. Engineering and styling worked together to make sure the system is not only designed and carefully tested to work superbly, but that it is also engineered not to interfere with style. ABS is an option on all 2016 Sportster® models.

[2] North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

2016 SEVENTY-TWO®
XL 1200V
MODEL SPECIFICATIONS[1]

Specifications apply to all available markets unless noted.

DIMENSIONS

Length	**2275 mm** (89.6 in.)
Overall Width	**920 mm** (36.2 in.)
Overall Height	**1265 mm** (49.8 in.)
Seat Height *(unladen)*	**730 mm** (28.7 in.)
Ground Clearance	**130 mm** (5.1 in.)
Rake *(steering head)*	32.1°
Fork Angle	32.1°
Trail	**135 mm** (5.3 in.)
Wheelbase	**1540 mm** (60.6 in.)
Tires *(Dunlop® Harley-Davidson® Series, narrow whitewall)*:	
• Front – D402F	MH90-21 54H
• Rear – D401	150/80B16 71H
Fuel Capacity *(warning light at approximately 2.5 L)*	**7.9 L** (2.1 gal.)
Oil Capacity *(w/filter)*	**2.6 L** (2.8 qts.)
Transmission Capacity	**.95 L** (1 qt.)
Weight:	
• As Shipped	**251 kg** (553 lbs.)
• In Running Order	**257 kg** (567 lbs.)
• Gross Vehicle Weight Rating	**454 kg** (1000 lbs.)
• Gross Axle Weight Rating	
• Front	**152 kg** (335 lbs.)
• Rear	**302 kg** (665 lbs.)

ENGINE

Engine	Air-cooled, Evolution®
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	**88.9 mm x 96.8 mm** (3.5 in. x 3.811 in.)
Displacement	**1202 cc** (73.4 cu. in.)
Compression Ratio	10:1
Fuel System[2]	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Paper cartridge type
Lubrication System	Dry-sump

DRIVETRAIN

Primary Drive	Chain, 38/57 ratio
Final Drive:	Belt, 30/68 ratio
Clutch	Multi-plate, wet
Transmission	5-speed
Gear Ratios *(overall)*:	
• 1st	**9.004**
• 2nd	**6.432**
• 3rd	**4.783**
• 4th	**3.965**
• 5th	**3.4**

CHASSIS

Frame	Mild steel, tubular frame; circular sections; cast junctions
Swingarm	Mild steel, rectangular tube section, stamped junctions; MIG welded
Front Forks	39 mm
Rear Shocks	Dual Coil-Over; Threaded Preload Adjustment, Emulsion
Wheels[3]:	Chrome Steel Laced with Custom Whitewall Tires
• Front	**21 in. x 2.15 in.** (533 mm x 55 mm)
• Rear	**16 in. x 3 in.** (406 mm x 76 mm)
Brakes:	
• Caliper Type	Dual-piston front, dual-piston rear
• Rotor Type *(diameter x width)*:	Solid, uniform expansion rotors
• Front	**300 mm x 5 mm** (11.8 in. x 0.2 in.)
• Rear	**260 mm x 7.1 mm** (10.24 in. x 0.28 in.)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	**140 mm** (5.51 in.)
• Rear Wheel	**54 mm** (2.13 in.)

PERFORMANCE

Engine Torque[4]:	
• AUS *(per EEC/95/1)*	**97 Nm** (71.5 ft-lb) **@ 3250 RPM**
Lean Angle *(per J1168)*:	
• Right	28.6°
• Left	29.8°
Fuel Economy[5] *(EPA urban/highway test)*	**4.9 L/100 km** (48 mpg)

ELECTRIC

Battery *(per Battery Council International Rating)*	Sealed, maintenance-free, 12V, 12 amp/hour, 200 cca
Charging	Single-phase, 30-amp system *(357W @ 13.5V, 2000 RPM, 405W max power @ 13.5V)*
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights *(as per country regulation)*:	
• Headlamp *(Quartz Halogen)*	55-watt low beam, 60-watt high beam
• Indicator Lamps	High beam, neutral, low oil pressure, turn signals, engine diagnostics, low fuel warning, low battery, security system[6] *(optional - AUS)*, ABS

WARRANTY

Warranty	24 months *(unlimited mileage)*
Service Interval[7]	First **1600 km** (1000 miles), every **8000 km** (5000 miles) thereafter

[1] Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

[2] Recommended 91 octane or higher fuel (R+M)/2.

[3] Standard and optional wheels may vary by country and region.

[4] Values shown are nominal. Performance may vary by country and region.

[5] The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

[6] North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

[7] Inspections of certain systems and components are required at 4000 km (2500 mile) intervals. See Owner's Manual for full details.

2016 SEVENTY-TWO®
XL 1200V
COLORS/CALLOUTS

SOLIDS
Black Denim
Black Quartz
NEW Charcoal Denim

HARD CANDY CUSTOM™ COLORS[1]
NEW Hard Candy Gold Flake
NEW **Hard Candy Black Gold Flake** *(shown)*

* Availability of colors may vary from dealer to dealer, and is subject to change without notice.
[1] Limited availability. See your dealer for details and available colors.

Model shown in Domestic configuration.

