2016 STREET BOB®

FXDB

A Minimalist Bobber, Featuring Optional H-DI™ Factory Customization.

Model shown in HDI configuration.

The vehicle models, configurations, options, and accessories pictured or otherwise described in this reference guide may not be available in all countries.



Markets: APC, AUS, BRZ, MEX, ENG, HDI, IND, JPN

2016 STREET BOB®

FXDB

MODEL OVERVIEW

MODEL OVERVIEW

The Street Bob® motorcycle oozes cool with tough looks that go straight back to the roots of the bobber scene. The model leaves everything exposed and is as “naked” as the law allows. There’s not a part on it that isn’t absolutely necessary, yet it’s also premium in every way.

NEW IN 2016

- Paint color options including Hard Candy Custom™ colors

MODEL UNIQUE FEATURES

Style
- Blacked-out powertrain with polished highlights
- Chrome, staggered exhaust with tapered mufflers
- Black Steel Laced wheels
- Chopped rear fender with no support covers
- Nostalgic air cleaner cover
- Internally-wired handlebar

MODEL UNIQUE FEATURES *(continued)*

Fit
- Stainless steel, mini ape-hanger handlebar
- Mid-mounted foot controls
- Solo seat
- Low 648 mm seat height

Function
- Tank-mounted electronic speedometer with odometer, time-of-day clock on odometer, dual tripmeter, RPM/gear display, fuel gauge with low-fuel warning light and countdown feature, low oil pressure indicator light, engine diagnostics readout, LED indicator lights, 6-speed indicator light
- Start, engine cutoff, left/right turn signals, horn, hi/low beam with flash-to-pass hand controls
- Self-canceling turn signal controls with integrated hazard warning
- Barrel key, console-mounted ignition
- 19-inch front, 17-inch rear wheels
- Michelin® Scorcher® tires

Performance
- Rubber-mounted, Air-cooled, 1690 cc Twin Cam 103™ engine
- 6-Speed Cruise Drive® transmission
- Electronic Sequential Port Fuel Injection (ESPFI)

AVAILABLE OPTIONS

- Anti-lock Braking System (ABS)[1] (factory installed option), standard
- Smart Security System[2] with proximity-based, hands-free security fob (factory installed option)
- Engine Idle Temperature Management Strategy (EITMS) (dealer-activated option)
- H-D1™ Factory Customization options available:
  - Seat
  - Handlebar
  - Wheels/finishes
  - Foot controls
  - Paint and graphics
  - Engine finish
- ABS and the Smart Security System are also available as options on H-D1™ models

[1] Harley-Davidson’s independent Anti-lock Braking System is designed to help you maintain control during braking events, especially those that happen in less than optimum conditions. Engineering and styling worked together to make sure the system is not only designed and carefully tested to work superbly, but that it is also engineered not to interfere with style.

[2] North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

2016 STREET BOB®
FXDB
MODEL SPECIFICATIONS[1]

Specifications apply to all available markets unless noted.

DIMENSIONS

Length	**2395 mm** (94.3 in.)
Overall Width	**915 mm** (36 in.)
Overall Height	**1240 mm** (48.8 in.)
Seat Height *(unladen)*	**680 mm** (26.8 in.)
Ground Clearance	**120 mm** (4.7 in.)
Rake *(steering head)*	29°
Fork Angle	29°
Trail	**119 mm** (4.7 in.)
Wheelbase	**1630 mm** (64.2 in.)
Tires *(Michelin® Scorcher® "31" front and rear)*:	
• Front – Scorcher® "31"	100/90B19 57H
• Rear – Scorcher® "31"	160/70B17 73V
Fuel Capacity *(warning light at approximately 3.4 L)*	**17.8 L** (4.7 gal.)
Oil Capacity *(w/filter)*	**2.8 L** (3 qts.)
Transmission Capacity	**.95 L** (1 qt.)
Primary Chain Case Capacity	**.95 L** (1 qt.)
Weight:	
• As Shipped	**291 kg** (642 lbs.)
• In Running Order	**304 kg** (670 lbs.)
• Gross Vehicle Weight Rating	**492 kg** (1085 lbs.)
• Gross Axle Weight Rating:	
• Front	**177 kg** (390 lbs.)
• Rear	**315 kg** (695 lbs.)

ENGINE

Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	**98.4 mm x 111.1 mm** (3.875 in. x 4.375 in.)
Displacement	**1690 cc** (103.1 cu. in.)
Compression Ratio	9.6:1
Fuel System[2]	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass Media, washable
Lubrication System	Pressurised, dry-sump

DRIVETRAIN

Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-speed Cruise Drive®
Gear Ratios *(overall)*:	
• 1st	**9.311**
• 2nd	**6.454**
• 3rd	**4.793**
• 4th	**3.882**
• 5th	**3.307**
• 6th	**2.79**

CHASSIS

Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Coil-over shock
Wheels[3]:	Black Steel Laced
• Front	**19 in. x 2.5 in.** (483 mm x 64 mm)
• Rear	**17 in. x 4.5 in.** (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type *(diameter x width)*:	Patented, uniform expansion rotors (floating, front only)
• Front *(floating)*	**300 mm x 5.1 mm** (11.8 in. x 0.2 in.)
• Rear	**292 mm x 5.8 mm** (11.5 in. x 0.23 in.)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	**127 mm** (5 in.)
• Rear Wheel	**80 mm** (3.1 in.)

PERFORMANCE

Engine Torque[4]:	
• HDI *(per EEC/95/1)*	**130 Nm** (95.9 ft-lb) **@ 3000 RPM**
Lean Angle *(per J1168)*:	
• Right	30°
• Left	31°
Fuel Economy[5] *(EPA urban/highway test)*	**5.5 L/100 km** (43 mpg)

ELECTRIC

Battery *(per Battery Council International Rating)*	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system *(493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)*
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights *(as per country regulation)*:	
• Headlamp *(Quartz Halogen)*	55-watt low beam, 60-watt high beam
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system[6], 6-speed, low fuel warnings
• Electric Power Outlet	Standard

WARRANTY

Warranty	24 months *(unlimited mileage)*
Service Interval[7]	First **1600 km** (1000 miles), every **8000 km** (5000 miles) thereafter

[1] Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

[2] Recommended 91 octane or higher fuel (R+M)/2.

[3] Standard and optional wheels may vary by country and region.

[4] Values shown are nominal. Performance may vary by country and region.

[5] The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

[6] North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

[7] Inspections of certain systems and components are required at 4000 km (2500 mile) intervals. See Owner's Manual for full details.

2016 STREET BOB®

FXDB

COLORS/CALLOUTS

SOLIDS
Vivid Black
Charcoal Pearl
Black Denim
NEW Crushed Ice Pearl
NEW Velocity Red Sunglo
NEW **Olive Gold** *(shown)*

TWO-TONES	PINSTRIPING
NEW Billet Silver/Vivid Black	Burgundy

HARD CANDY CUSTOM™ COLORS[1]
Hard Candy Cancun Blue Flake

* Availability of colors may vary from dealer to dealer, and is subject to change without notice.

[1] Limited availability. See your dealer for details and available colors.

Model shown in Domestic configuration.

